

## G Series 1-18W Recessed IP Rated

G Series Recessed fixtures are IP67 Rated and suitable for both indoor and outdoor installation. All G Series recessed are supplied with in concrete housings and both the SS and SR can also be mounted in ceilings if required.



G11SRCW30  
G13SRCW30



G11SSCW30  
G13SSCW30

### ELECTRONIC SPECIFICATIONS

PARAMETERS	G-Series
<b>ELECTRICAL:</b>	
Power Supply Voltage (Typ.)	24VAC/DC
Power Supply Current	<500mA
Power Consumption	< 5W
<b>OPTICAL:</b>	
Operating Life	>35,000 hrs.
Beam Angle:	30°
<b>ENVIRONMENT:</b>	
Operation Temperature	-20~50°C
Storage Temperature	-40~60°C
IP Rating	IP67

Model	Lumen Output (lm)	Color Temperature	Beam Angle
G11SRWW30	70lm ± 10%	3000K	30°
G11SRCW30	80lm ± 10%	5000K	30°
G11SSWW30	70lm ± 10%	3000K	30°
G11SSCW30	80lm ± 10%	5000K	30°
G13RWW30	120lm ± 10%	3000K	30°
G13RCW30	130lm ± 10%	5000K	30°
G13SWW30	120lm ± 10%	3000K	30°
G13SCW30	130lm ± 10%	5000K	30°

### G Series Outline

#### Features

- High power 1W and 3W Titan Emitters.
- In concrete housings included.
- Min. 70% lumen maintenance greater than 35,000 hours
- Stainless steel surround and Toughened glass.
- Low thermal radiation and zero UV radiation.



G11RCW30  
G13RCW30



G11SCW30  
G13SCW30