

# G Series 1-18W Recessed IP Rated

G Series Recessed fixtures are IP67 Rated and suitable for both indoor and outdoor installation. All G Series recessed are supplied with in concrete housings and both the SS and SR can also be mounted in ceilings if required.



G31RCW30  
G33RCW30

## ELECTRONIC SPECIFICATIONS

PARAMETERS	G-Series
<b>ELECTRICAL:</b>	
Power Supply Voltage (Typ.)	24VAC/DC
Power Supply Current	<800mA
Power Consumption	< 18W
<b>OPTICAL:</b>	
Operating Life	>35,000 hrs.
Beam Angle:	30°
<b>ENVIRONMENT:</b>	
Operation Temperature	-20~50°C
Storage Temperature	-40~60°C
IP Rating	IP67

Model	Lumen Output (lm)	Color Temperature	Beam Angle
G31RWW30	210lm ± 10%	3000K	30°
G31RCW30	240lm ± 10%	5000K	30°
G61RWW30	420lm ± 10%	3000K	30°
G61RCW30	480lm ± 10%	5000K	30°
G33RWW30	360lm ± 10%	3000K	30°
G33RCW30	390lm ± 10%	5000K	30°
G63RWW30	720lm ± 10%	3000K	30°
G63RCW30	780lm ± 10%	5000K	30°

## G Series Outline

### Features

- High power 1W and 3W Titan Emitters.
- In concrete housings included.
- Min. 70% lumen maintenance greater than 35,000 hours
- Stainless steel surround and Toughened glass.
- Low thermal radiation and zero UV radiation.



G61RCW30  
G63RCW30